


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.5V I:0.1738A P:37.10W PF:0.9679 Lamp Flux:3754.04x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 101.18 lm/W			
MODEL	PL-6262-36D	Imax(cd)	1699	S/MH(C0/180)	1.26
NOMINAL POWER(W)	36	LOR(%)	100.0	S/MH(C90/270)	1.23
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	3754.0	η UP,DN(C0-180)	0.1,49.9
NOMINAL FLUX(lm)	3754.04	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.1,49.9
LAMPS INSIDE	1	η up(%)	0.2	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	220	η down(%)	99.8	CIBSE SHR MAX	1.25

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=0.9590]
 Remarks:

ZONAL FLUX DIAGRAM AND LUMINANCE LIMITATION CURVES

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	$\%lum, lamp$
10	1688	1692	1697	1693	1689	1693	1697	1692	0- 10	161.8	161.8	4.31,4.31
20	1638	1653	1674	1654	1628	1654	1674	1653	10- 20	474.9	636.7	17,17
30	1488	1521	1567	1528	1476	1528	1567	1521	20- 30	737.4	1374	36.6,36.6
40	1165	1068	1064	1032	1105	1032	1064	1068	30- 40	840.5	2215	59,59
50	674.7	643.3	589.4	645.8	689.2	645.8	589.4	643.3	40- 50	632.6	2847	75.8,75.8
60	283.7	379.6	318.3	366.3	284.3	366.3	318.3	379.6	50- 60	424.8	3272	87.2,87.2
70	216.0	191.1	194.5	181.5	213.1	181.5	194.5	191.1	60- 70	255.8	3528	94,94
80	102.5	104.8	101.8	110.5	117.6	110.5	101.8	104.8	70- 80	160.5	3688	98.2,98.2
90	0.6637	0.4833	0.5075	0.3927	0.5205	0.3927	0.5075	0.4833	80- 90	58.96	3747	99.8,99.8
100	0.3314	0.3396	0.3231	0.3230	0.3229	0.3230	0.3231	0.3396	90-100	0.3461	3748	99.8,99.8
110	0.5216	0.5383	0.5095	0.5257	0.5256	0.5257	0.5095	0.5383	100-110	0.4590	3748	99.8,99.8
120	0.8408	0.8734	0.8446	0.8613	0.8612	0.8613	0.8446	0.8734	110-120	0.6895	3749	99.9,99.9
130	1.221	1.275	1.284	1.271	1.255	1.271	1.284	1.275	120-130	0.9654	3750	99.9,99.9
140	1.561	1.636	1.652	1.632	1.602	1.632	1.652	1.636	130-140	1.134	3751	99.9,99.9
150	1.930	2.000	2.001	1.996	1.959	1.996	2.001	2.000	140-150	1.140	3752	99.9,99.9
160	2.357	2.386	2.411	2.398	2.385	2.398	2.411	2.386	150-160	1.017	3753	100,100
170	2.667	2.680	2.688	2.696	2.680	2.696	2.688	2.680	160-170	0.7253	3754	100,100
180	2.812	2.804	2.792	2.808	2.812	2.808	2.792	2.804	170-180	0.2628	3754	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=0.9590]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.5V I:0.1738A P:37.10W PF:0.9679 Lamp Flux:3754.04x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.06	1.02	.99	1.04	1.00	.97	.99	.97	.94	.96	.93	.91	.92	.90	.89	.87
2.0	.94	.88	.83	.92	.87	.82	.89	.84	.80	.86	.82	.79	.83	.80	.77	.75
3.0	.84	.77	.71	.83	.76	.71	.80	.74	.70	.77	.72	.68	.75	.71	.67	.65
4.0	.76	.68	.62	.75	.67	.62	.72	.66	.61	.70	.65	.60	.68	.63	.59	.57
5.0	.69	.61	.55	.68	.60	.54	.66	.59	.54	.64	.58	.53	.62	.57	.53	.51
6.0	.63	.54	.49	.62	.54	.48	.60	.53	.48	.58	.52	.48	.57	.51	.47	.45
7.0	.57	.49	.44	.57	.49	.43	.55	.48	.43	.54	.47	.43	.52	.47	.43	.41
8.0	.53	.45	.39	.52	.44	.39	.51	.44	.39	.49	.43	.39	.48	.43	.39	.37
9.0	.49	.41	.36	.48	.41	.36	.47	.40	.36	.46	.40	.35	.45	.39	.35	.33
10.0	.45	.38	.33	.45	.37	.33	.44	.37	.32	.43	.37	.32	.42	.36	.32	.31



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9590]
 Remarks:

WEC AND CCEC

Test:U:220.5V I:0.1738A P:37.10W PF:0.9679 Lamp Flux:3754.04x1 lm								
NAME: Panel light			TYPE:LED			WEIGHT:		
SPEC.:6262			DIM.: 620*620			SERIAL No.:1		
MFR.: JT			SUR.:0.62*0.62			Shielding Angle:		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.269	.153	.048	.262	.149	.047	.249	.143	.046	.237	.137	.044	.226	.131	.042	
2.0	.254	.139	.043	.248	.137	.042	.236	.131	.041	.226	.127	.040	.216	.122	.039	
3.0	.237	.126	.038	.232	.124	.037	.222	.120	.037	.213	.117	.036	.204	.113	.035	
4.0	.221	.115	.034	.217	.113	.034	.208	.110	.033	.200	.107	.032	.192	.104	.032	
5.0	.207	.105	.031	.203	.104	.030	.195	.101	.030	.187	.099	.029	.181	.097	.029	
6.0	.194	.097	.028	.190	.096	.028	.183	.094	.027	.176	.092	.027	.170	.090	.027	
7.0	.182	.090	.025	.179	.089	.025	.172	.087	.025	.166	.085	.025	.161	.084	.025	
8.0	.171	.084	.024	.168	.083	.023	.163	.081	.023	.157	.080	.023	.152	.078	.023	
9.0	.161	.078	.022	.159	.077	.022	.154	.076	.022	.149	.075	.021	.145	.073	.021	
10.0	.153	.073	.020	.150	.073	.020	.146	.071	.020	.142	.070	.020	.138	.069	.020	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.192	.192	.192	.164	.164	.164	.112	.112	.112	.064	.064	.064	.021	.021	.021	
1.0	.179	.158	.139	.153	.135	.120	.105	.093	.083	.060	.054	.048	.019	.017	.016	
2.0	.169	.133	.104	.144	.115	.090	.099	.079	.063	.057	.046	.037	.018	.015	.012	
3.0	.160	.115	.080	.137	.100	.070	.094	.069	.049	.054	.040	.029	.017	.013	.009	
4.0	.151	.102	.064	.130	.088	.055	.089	.061	.039	.052	.036	.023	.017	.012	.008	
5.0	.144	.091	.052	.124	.079	.045	.085	.055	.032	.049	.032	.019	.016	.011	.006	
6.0	.137	.082	.043	.118	.071	.038	.081	.050	.027	.047	.029	.016	.015	.010	.005	
7.0	.130	.075	.037	.112	.065	.032	.078	.046	.023	.045	.027	.014	.015	.009	.004	
8.0	.124	.070	.032	.107	.060	.028	.074	.042	.020	.043	.025	.012	.014	.008	.004	
9.0	.119	.065	.028	.102	.056	.025	.071	.039	.017	.041	.023	.010	.013	.008	.003	
10.0	.113	.060	.025	.098	.052	.022	.068	.037	.016	.040	.022	.009	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9590]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.5V I:0.1738A P:37.10W PF:0.9679 Lamp Flux:3754.04x1 lm										
NAME: Panel light					TYPE:LED			WEIGHT:		
SPEC.:6262					DIM.: 620*620			SERIAL No.:1		
MFR.: JT					SUR.:0.62*0.62			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	14.9	16.3	15.2	16.5	16.7	14.7	16.0	14.9	16.2	16.4
3H	15.8	17.1	16.1	17.3	17.5	15.5	16.7	15.8	16.9	17.2
4H	16.3	17.5	16.6	17.8	18.0	15.9	17.1	16.2	17.3	17.6
6H	16.7	17.9	17.1	18.1	18.4	16.3	17.5	16.7	17.7	18.0
8H	16.9	18.0	17.3	18.3	18.6	16.6	17.6	16.9	17.9	18.2
12H	17.0	18.1	17.4	18.4	18.7	16.8	17.8	17.1	18.1	18.4
4H 2H	15.2	16.4	15.5	16.7	16.9	15.0	16.2	15.3	16.5	16.7
3H	16.4	17.4	16.7	17.7	18.0	16.0	17.1	16.4	17.4	17.7
4H	17.0	18.0	17.4	18.3	18.6	16.6	17.6	17.0	17.9	18.2
6H	17.6	18.4	18.0	18.8	19.1	17.3	18.1	17.7	18.4	18.8
8H	17.8	18.6	18.3	19.0	19.4	17.6	18.3	18.0	18.7	19.1
12H	18.0	18.7	18.4	19.1	19.5	17.8	18.6	18.3	18.9	19.3
8H 4H	17.2	18.0	17.6	18.4	18.7	16.9	17.7	17.3	18.0	18.4
6H	18.0	18.6	18.4	19.0	19.4	17.7	18.3	18.1	18.7	19.2
8H	18.3	18.9	18.8	19.3	19.8	18.1	18.7	18.6	19.1	19.6
12H	18.6	19.1	19.1	19.5	20.0	18.5	19.0	19.0	19.5	19.9
12H 4H	17.2	18.0	17.7	18.3	18.7	16.9	17.6	17.3	18.0	18.4
6H	18.0	18.6	18.5	19.0	19.5	17.8	18.4	18.2	18.8	19.2
8H	18.4	18.9	18.9	19.4	19.9	18.3	18.8	18.7	19.2	19.7
Variations with the observer position at spacings:										
S = 1.0H	+ 0.3 / - 0.5					+ 0.4 / - 0.4				
1.5H	+ 0.2 / - 0.3					+ 0.3 / - 0.2				
2.0H	+ 0.7 / - 1.0					+ 0.6 / - 0.7				

CIE Pub.117 Corrected 3754 lm Total Lamp Luminous Flux.(8log(F/F0) = 4.6)

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9590]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.5V I:0.1738A P:37.10W PF:0.9679 Lamp Flux:3754.04x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	66	56	50	65	56	50	64	55	50	44
0.80	76	66	59	75	65	59	73	65	59	53
1.00	83	74	68	82	73	67	80	74	67	61
1.25	90	81	75	88	80	74	86	79	74	67
1.50	94	86	80	92	85	79	90	83	78	72
2.00	99	92	87	98	91	86	94	89	85	78
2.50	103	96	91	101	95	90	97	92	88	81
3.00	105	100	95	103	98	94	99	95	92	84
4.00	109	104	100	106	102	98	102	99	96	87
5.00	110	106	103	108	104	101	104	101	98	90
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9590]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.5V I:0.1738A P:37.10W PF:0.9679 Lamp Flux:3754.04x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

Conical surface Flux(90deg):

2560.2 lm

%lum = 68.2%


%lamp = 68.2%

Conical surface Flux(120deg):

3272 lm

%lum = 87.2%

%lamp = 87.2%




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:ZYP
Test Date:2020-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:25%
Test Distance:7.560m [K=0.9590]
Remarks:

AAI Figure

Test:U:220.5V I:0.1738A P:37.10W PF:0.9679 Lamp Flux:3754.04x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=0.9590]
 Remarks:

ISOLUX DIAGRAM

Test:U:220.5V I:0.1738A P:37.10W PF:0.9679 Lamp Flux:3754.04x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9590]
 Remarks:

LED Avg.L Report

Test:U:220.5V I:0.1738A P:37.10W PF:0.9679 Lamp Flux:3754.04x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	1527
L_0~180(75)av	1655
L_0~180(85)av	1578
L_90~270(65)av	1608
L_90~270(75)av	1413
L_90~270(85)av	1868
L_45(65)av	1618
L_45(75)av	1497
L_45(85)av	1695

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9590]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: ZYP
Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 25%
Test Distance: 7.560m [K=0.9590]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.5V I:0.1738A P:37.10W PF:0.9679 Lamp Flux:3754.04x1 lm																		
NAME: Panel light									TYPE:LED					WEIGHT:				
SPEC.:6262									DIM.: 620*620					SERIAL No.:1				
MFR.: JT									SUR.:0.62*0.62					Shielding Angle:				

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1695	1695	1695	1695	1695	1695	1694	1696	1696	1696	1694	1695	1695	1695	1695	1695			
5	1694	1694	1695	1696	1696	1698	1696	1697	1696	1697	1696	1698	1696	1696	1695	1694			
10	1688	1687	1692	1696	1697	1698	1693	1689	1689	1689	1693	1698	1697	1696	1692	1687			
15	1672	1668	1679	1689	1689	1693	1681	1667	1668	1667	1681	1693	1689	1689	1679	1668			
20	1638	1634	1653	1669	1674	1671	1654	1635	1628	1635	1654	1671	1674	1669	1653	1634			
25	1573	1576	1601	1625	1633	1627	1602	1576	1561	1576	1602	1627	1633	1625	1601	1576			
30	1488	1494	1521	1563	1567	1560	1528	1490	1476	1490	1528	1560	1567	1563	1521	1494			
35	1383	1366	1374	1405	1399	1383	1367	1353	1356	1353	1367	1383	1399	1405	1374	1366			
40	1165	1126	1068	1058	1064	1040	1032	1089	1105	1089	1032	1040	1064	1058	1068	1126			
45	892	826	812	812	749	816	797	772	859	772	797	816	749	812	812	826			
50	675	614	643	618	589	640	646	587	689	587	646	640	589	618	643	614			
55	455	483	516	444	459	465	462	493	444	493	462	465	459	444	516	483			
60	284	385	380	323	318	350	366	326	284	326	366	350	318	323	380	385			
65	223	273	275	255	258	227	245	263	267	263	245	227	258	255	275	273			
70	216	221	191	181	194	177	182	206	213	206	182	177	194	181	191	221			
75	166	154	145	153	139	151	150	159	160	159	150	151	139	153	145	154			
80	103	104	105	109	102	113	111	95.1	118	95.1	111	113	102	109	105	104			
85	50.2	52.1	56.6	59.1	61.9	64.3	55.7	48.2	54.4	48.2	55.7	64.3	61.9	59.1	56.6	52.1			
90	0.66	0.68	0.48	0.66	0.51	0.36	0.39	0.36	0.52	0.36	0.39	0.36	0.51	0.66	0.48	0.68			
95	0.29	0.32	0.30	0.31	0.28	0.31	0.29	0.31	0.29	0.31	0.29	0.31	0.28	0.31	0.30	0.32			
100	0.33	0.38	0.34	0.36	0.32	0.36	0.32	0.37	0.32	0.37	0.32	0.36	0.32	0.36	0.34	0.38			
105	0.41	0.46	0.42	0.44	0.41	0.44	0.41	0.45	0.41	0.45	0.41	0.44	0.41	0.44	0.42	0.46			
110	0.52	0.57	0.54	0.56	0.51	0.55	0.53	0.57	0.53	0.57	0.53	0.55	0.51	0.56	0.54	0.57			
115	0.67	0.72	0.68	0.71	0.66	0.70	0.68	0.72	0.67	0.72	0.68	0.70	0.66	0.71	0.68	0.72			
120	0.84	0.89	0.87	0.89	0.84	0.89	0.86	0.89	0.86	0.89	0.86	0.89	0.84	0.89	0.87	0.89			
125	1.03	1.09	1.07	1.11	1.06	1.10	1.07	1.11	1.06	1.11	1.07	1.10	1.06	1.11	1.07	1.09			
130	1.22	1.29	1.28	1.31	1.28	1.32	1.27	1.31	1.25	1.31	1.27	1.32	1.28	1.31	1.28	1.29			
135	1.40	1.46	1.45	1.50	1.47	1.51	1.45	1.48	1.42	1.48	1.45	1.51	1.47	1.50	1.45	1.46			
140	1.56	1.65	1.64	1.68	1.65	1.68	1.63	1.66	1.60	1.66	1.63	1.68	1.65	1.68	1.64	1.65			
145	1.74	1.83	1.81	1.85	1.83	1.86	1.81	1.84	1.77	1.84	1.81	1.86	1.83	1.85	1.81	1.83			
150	1.93	2.02	2.00	2.03	2.00	2.03	2.00	2.03	1.96	2.03	2.00	2.03	2.00	2.03	2.00	2.02			
155	2.14	2.22	2.19	2.23	2.20	2.24	2.20	2.23	2.17	2.23	2.20	2.24	2.20	2.23	2.19	2.22			
160	2.36	2.43	2.39	2.44	2.41	2.44	2.40	2.44	2.39	2.44	2.40	2.44	2.41	2.44	2.39	2.43			
165	2.53	2.59	2.56	2.61	2.58	2.61	2.57	2.61	2.56	2.61	2.57	2.61	2.58	2.61	2.56	2.59			
170	2.67	2.71	2.68	2.73	2.69	2.74	2.70	2.73	2.68	2.73	2.70	2.74	2.69	2.73	2.68	2.71			
175	2.76	2.78	2.76	2.79	2.75	2.80	2.77	2.80	2.77	2.80	2.77	2.80	2.75	2.79	2.76	2.78			
180	2.81	2.81	2.80	2.81	2.79	2.80	2.81	2.81	2.81	2.81	2.81	2.80	2.79	2.81	2.80	2.81			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9590]
 Remarks: