


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.5V I:0.1751A P:37.41W PF:0.9685 Lamp Flux:3853.59x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 103.02 lm/W			
MODEL	PL-6262-36D	Imax(cd)	1744	S/MH(C0/180)	1.26
NOMINAL POWER(W)	36	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	3853.6	η UP,DN(C0-180)	0.1,49.9
NOMINAL FLUX(lm)	3853.59	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.1,49.9
LAMPS INSIDE	1	η up(%)	0.2	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	220	η down(%)	99.8	CIBSE SHR MAX	1.25

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:ZYP
Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:25%
Test Distance:7.560m [K=0.9788]
Remarks:

ZONAL FLUX DIAGRAM AND LUMINANCE LIMITATION CURVES

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	Φ lum, lamp
10	1734	1738	1742	1738	1733	1738	1742	1738	0- 10	166.1	166.1	4.31,4.31
20	1684	1699	1720	1695	1670	1695	1720	1699	10- 20	487.6	653.7	17,17
30	1529	1565	1610	1565	1516	1565	1610	1565	20- 30	757.1	1411	36.6,36.6
40	1203	1092	1095	1066	1141	1066	1095	1092	30- 40	864.2	2275	59,59
50	693.0	662.7	606.9	664.7	708.5	664.7	606.9	662.7	40- 50	650.6	2926	75.9,75.9
60	286.9	387.1	323.7	385.2	287.8	385.2	323.7	387.1	50- 60	435.7	3361	87.2,87.2
70	219.6	189.5	198.0	188.5	219.4	188.5	198.0	189.5	60- 70	260.6	3622	94,94
80	104.1	109.4	105.3	113.6	122.2	113.6	105.3	109.4	70- 80	164.5	3786	98.3,98.3
90	0.6692	0.4767	0.5073	0.4057	0.5056	0.4057	0.5073	0.4767	80- 90	60.29	3847	99.8,99.8
100	0.3407	0.3537	0.3280	0.3365	0.3320	0.3365	0.3280	0.3537	90-100	0.3604	3847	99.8,99.8
110	0.5348	0.5520	0.5262	0.5434	0.5348	0.5434	0.5262	0.5520	100-110	0.4726	3848	99.8,99.8
120	0.8672	0.8889	0.8715	0.8885	0.8803	0.8885	0.8715	0.8889	110-120	0.7074	3848	99.9,99.9
130	1.255	1.307	1.316	1.307	1.281	1.307	1.316	1.307	120-130	0.9900	3849	99.9,99.9
140	1.609	1.669	1.691	1.670	1.635	1.670	1.691	1.669	130-140	1.163	3850	99.9,99.9
150	1.989	2.050	2.050	2.041	2.010	2.041	2.050	2.050	140-150	1.168	3852	99.9,99.9
160	2.429	2.446	2.472	2.463	2.442	2.463	2.472	2.446	150-160	1.042	3853	100,100
170	2.731	2.744	2.753	2.766	2.731	2.766	2.753	2.744	160-170	0.7434	3853	100,100
180	2.883	2.870	2.861	2.870	2.878	2.870	2.861	2.870	170-180	0.2694	3854	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=0.9788]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.5V I:0.1751A P:37.41W PF:0.9685 Lamp Flux:3853.59x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0														
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
pfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Coefficients of Utilization(CU)														
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00														
1.0	1.06	1.02	.99	1.04	1.00	.97	.99	.97	.94	.96	.93	.91	.92	.90	.89	.87														
2.0	.94	.88	.83	.92	.87	.82	.89	.84	.80	.86	.82	.79	.83	.80	.77	.75														
3.0	.84	.77	.71	.83	.76	.71	.80	.74	.70	.77	.72	.68	.75	.71	.67	.65														
4.0	.76	.68	.62	.75	.67	.62	.72	.66	.61	.70	.65	.60	.68	.63	.59	.57														
5.0	.69	.61	.55	.68	.60	.54	.66	.59	.54	.64	.58	.53	.62	.57	.53	.51														
6.0	.63	.54	.49	.62	.54	.48	.60	.53	.48	.58	.52	.48	.57	.51	.47	.45														
7.0	.57	.49	.44	.57	.49	.43	.55	.48	.43	.54	.47	.43	.52	.47	.43	.41														
8.0	.53	.45	.39	.52	.44	.39	.51	.44	.39	.50	.43	.39	.48	.43	.39	.37														
9.0	.49	.41	.36	.48	.41	.36	.47	.40	.36	.46	.40	.35	.45	.39	.35	.33														
10.0	.45	.38	.33	.45	.37	.33	.44	.37	.33	.43	.37	.32	.42	.36	.32	.31														



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9788]
 Remarks:

WEC AND CCEC

Test:U:220.5V I:0.1751A P:37.41W PF:0.9685 Lamp Flux:3853.59x1 lm					
NAME: Panel light			TYPE:LED		WEIGHT:
SPEC.:6262			DIM.: 620*620		SERIAL No.:1
MFR.: JT			SUR.:0.62*0.62		Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.269	.153	.048	.262	.149	.047	.249	.143	.046	.237	.136	.044	.225	.131	.042	
2.0	.254	.139	.043	.248	.136	.042	.236	.131	.041	.226	.127	.040	.216	.122	.039	
3.0	.237	.126	.038	.232	.124	.037	.222	.120	.037	.213	.116	.036	.204	.113	.035	
4.0	.221	.115	.034	.217	.113	.033	.208	.110	.033	.199	.107	.032	.192	.104	.032	
5.0	.207	.105	.031	.203	.104	.030	.195	.101	.030	.187	.099	.029	.181	.096	.029	
6.0	.194	.097	.028	.190	.096	.028	.183	.094	.027	.176	.092	.027	.170	.090	.027	
7.0	.182	.090	.025	.178	.089	.025	.172	.087	.025	.166	.085	.025	.161	.084	.025	
8.0	.171	.084	.024	.168	.083	.023	.163	.081	.023	.157	.080	.023	.152	.078	.023	
9.0	.161	.078	.022	.159	.077	.022	.154	.076	.022	.149	.075	.021	.145	.073	.021	
10.0	.153	.073	.020	.150	.073	.020	.146	.071	.020	.142	.070	.020	.137	.069	.020	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.192	.192	.192	.164	.164	.164	.112	.112	.112	.064	.064	.064	.021	.021	.021	
1.0	.179	.158	.139	.153	.135	.120	.105	.093	.083	.060	.054	.048	.019	.017	.016	
2.0	.169	.133	.104	.144	.115	.090	.099	.079	.063	.057	.046	.037	.018	.015	.012	
3.0	.160	.115	.080	.137	.100	.070	.094	.069	.049	.054	.040	.029	.017	.013	.009	
4.0	.151	.102	.064	.130	.088	.055	.089	.061	.039	.052	.036	.023	.017	.012	.008	
5.0	.144	.091	.052	.124	.079	.045	.085	.055	.032	.049	.032	.019	.016	.011	.006	
6.0	.137	.082	.043	.118	.071	.038	.081	.050	.027	.047	.029	.016	.015	.010	.005	
7.0	.130	.075	.037	.112	.065	.032	.077	.046	.023	.045	.027	.014	.015	.009	.004	
8.0	.124	.070	.032	.107	.060	.028	.074	.042	.020	.043	.025	.012	.014	.008	.004	
9.0	.119	.065	.028	.102	.056	.025	.071	.039	.017	.041	.023	.010	.013	.008	.003	
10.0	.113	.060	.025	.098	.052	.022	.068	.037	.016	.040	.022	.009	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9788]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.5V I:0.1751A P:37.41W PF:0.9685 Lamp Flux:3853.59x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	15.0	16.3	15.2	16.5	16.7	14.8	16.1	15.0	16.3	16.5
3H	15.8	17.1	16.1	17.3	17.6	15.6	16.8	15.8	17.0	17.3
4H	16.4	17.6	16.7	17.8	18.1	16.0	17.2	16.3	17.4	17.7
6H	16.8	17.9	17.1	18.2	18.4	16.4	17.5	16.8	17.8	18.1
8H	17.0	18.0	17.3	18.3	18.6	16.6	17.7	17.0	18.0	18.3
12H	17.1	18.1	17.4	18.4	18.7	16.8	17.9	17.2	18.2	18.5
4H 2H	15.3	16.5	15.6	16.7	17.0	15.1	16.3	15.4	16.5	16.8
3H	16.4	17.4	16.7	17.7	18.0	16.1	17.1	16.4	17.4	17.7
4H	17.1	18.0	17.4	18.3	18.7	16.7	17.6	17.1	18.0	18.3
6H	17.6	18.5	18.0	18.8	19.2	17.3	18.2	17.7	18.5	18.9
8H	17.9	18.7	18.3	19.0	19.4	17.6	18.4	18.1	18.8	19.2
12H	18.1	18.8	18.5	19.2	19.6	17.9	18.6	18.4	19.0	19.4
8H 4H	17.3	18.0	17.7	18.4	18.8	16.9	17.7	17.4	18.1	18.5
6H	18.0	18.6	18.4	19.0	19.5	17.8	18.4	18.2	18.8	19.3
8H	18.3	18.9	18.8	19.3	19.8	18.2	18.8	18.7	19.2	19.7
12H	18.6	19.1	19.1	19.6	20.0	18.6	19.1	19.1	19.6	20.0
12H 4H	17.3	18.0	17.7	18.4	18.8	17.0	17.7	17.4	18.1	18.5
6H	18.1	18.7	18.5	19.1	19.5	17.9	18.4	18.3	18.9	19.3
8H	18.5	19.0	19.0	19.4	19.9	18.4	18.8	18.8	19.3	19.8
Variations with the observer position at spacings:										
S = 1.0H	+ 0.3 / - 0.5					+ 0.4 / - 0.4				
1.5H	+ 0.2 / - 0.3					+ 0.3 / - 0.2				
2.0H	+ 0.7 / - 1.1					+ 0.6 / - 0.7				

CIE Pub.117 Corrected 3854 lm Total Lamp Luminous Flux.(8log(F/F0) = 4.7)

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9788]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.5V I:0.1751A P:37.41W PF:0.9685 Lamp Flux:3853.59x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	66	56	50	65	56	50	64	55	50	44
0.80	76	66	60	75	65	59	73	65	59	53
1.00	83	74	68	82	73	68	80	74	67	61
1.25	90	81	75	88	80	74	86	79	74	67
1.50	94	86	80	92	85	79	90	83	78	72
2.00	99	92	87	98	91	86	95	89	85	78
2.50	103	96	91	101	95	90	97	92	88	81
3.00	105	100	95	103	98	94	99	95	92	84
4.00	109	104	100	106	102	98	102	99	96	87
5.00	110	106	103	108	104	101	104	101	98	90
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9788]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.5V I:0.1751A P:37.41W PF:0.9685 Lamp Flux:3853.59x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

Conical surface Flux(90deg):

2630.5 lm

%lum = 68.3%


%lamp = 68.3%

Conical surface Flux(120deg):

3361.3 lm

%lum = 87.2%

%lamp = 87.2%




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:ZYP
Test Date:2020-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:25%
Test Distance:7.560m [K=0.9788]
Remarks:

AAI Figure

Test:U:220.5V I:0.1751A P:37.41W PF:0.9685 Lamp Flux:3853.59x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=0.9788]
 Remarks:

ISOLUX DIAGRAM

Test:U:220.5V I:0.1751A P:37.41W PF:0.9685 Lamp Flux:3853.59x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9788]
 Remarks:

LED Avg.L Report

Test:U:220.5V I:0.1751A P:37.41W PF:0.9685 Lamp Flux:3853.59x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	1538
L_0~180(75)av	1713
L_0~180(85)av	1608
L_90~270(65)av	1647
L_90~270(75)av	1443
L_90~270(85)av	1891
L_45(65)av	1638
L_45(75)av	1526
L_45(85)av	1707

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9788]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: ZYP
Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 25%
Test Distance: 7.560m [K=0.9788]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.5V I:0.1751A P:37.41W PF:0.9685 Lamp Flux:3853.59x1 lm																	
NAME: Panel light									TYPE:LED						WEIGHT:		
SPEC.:6262									DIM.: 620*620						SERIAL No.:1		
MFR.: JT									SUR.:0.62*0.62						Shielding Angle:		

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1742	1740	1741	1739	1740	1739	1739	1739	1740	1739	1739	1739	1740	1739	1741	1740			
5	1741	1739	1741	1743	1742	1742	1741	1740	1741	1740	1741	1742	1742	1743	1741	1739			
10	1734	1734	1738	1741	1742	1742	1738	1734	1733	1734	1738	1742	1742	1741	1738	1734			
15	1720	1712	1726	1733	1735	1737	1723	1710	1712	1710	1723	1737	1735	1733	1726	1712			
20	1684	1679	1699	1714	1720	1714	1695	1676	1670	1676	1695	1714	1720	1714	1699	1679			
25	1616	1620	1645	1671	1676	1668	1642	1617	1602	1617	1642	1668	1676	1671	1645	1620			
30	1529	1535	1565	1606	1610	1601	1565	1527	1516	1527	1565	1601	1610	1606	1565	1535			
35	1421	1404	1414	1446	1441	1423	1404	1387	1394	1387	1404	1423	1441	1446	1414	1404			
40	1203	1160	1092	1090	1095	1071	1066	1118	1141	1118	1066	1071	1095	1090	1092	1160			
45	916	847	836	837	768	841	816	793	883	793	816	841	768	837	836	847			
50	693	624	663	640	607	659	665	605	708	605	665	659	607	640	663	624			
55	466	494	528	462	466	469	481	511	449	511	481	469	466	462	528	494			
60	287	387	387	340	324	351	385	341	288	341	385	351	324	340	387	387			
65	224	271	276	259	264	229	251	272	270	272	251	229	264	259	276	271			
70	220	223	189	179	198	183	189	218	219	218	189	183	198	179	189	223			
75	172	159	148	157	142	156	153	162	165	162	153	156	142	157	148	159			
80	104	105	109	113	105	114	114	96.1	122	96.1	114	114	105	113	109	105			
85	51.9	50.4	57.4	62.1	62.6	65.9	55.7	50.8	54.6	50.8	55.7	65.9	62.6	62.1	57.4	50.4			
90	0.67	0.72	0.48	0.69	0.51	0.35	0.41	0.37	0.51	0.37	0.41	0.35	0.51	0.69	0.48	0.72			
95	0.30	0.33	0.32	0.32	0.30	0.32	0.30	0.32	0.30	0.32	0.30	0.32	0.30	0.32	0.32	0.33			
100	0.34	0.39	0.35	0.38	0.33	0.37	0.34	0.38	0.33	0.38	0.34	0.37	0.33	0.38	0.35	0.39			
105	0.42	0.47	0.44	0.46	0.41	0.45	0.42	0.47	0.42	0.47	0.42	0.45	0.41	0.46	0.44	0.47			
110	0.53	0.59	0.55	0.57	0.53	0.57	0.54	0.58	0.53	0.58	0.54	0.57	0.53	0.57	0.55	0.59			
115	0.68	0.73	0.70	0.73	0.68	0.72	0.69	0.74	0.69	0.74	0.69	0.72	0.68	0.73	0.70	0.73			
120	0.87	0.92	0.89	0.92	0.87	0.91	0.89	0.92	0.88	0.92	0.89	0.91	0.87	0.92	0.89	0.92			
125	1.07	1.12	1.10	1.13	1.09	1.13	1.09	1.13	1.08	1.13	1.09	1.13	1.09	1.13	1.10	1.12			
130	1.26	1.33	1.31	1.34	1.32	1.36	1.31	1.34	1.28	1.34	1.31	1.36	1.32	1.34	1.31	1.33			
135	1.44	1.51	1.49	1.54	1.50	1.54	1.48	1.52	1.46	1.52	1.48	1.54	1.50	1.54	1.49	1.51			
140	1.61	1.69	1.67	1.72	1.69	1.72	1.67	1.70	1.64	1.70	1.67	1.72	1.69	1.72	1.67	1.69			
145	1.79	1.87	1.85	1.90	1.87	1.89	1.85	1.88	1.82	1.88	1.85	1.89	1.87	1.90	1.85	1.87			
150	1.99	2.07	2.05	2.09	2.05	2.09	2.04	2.07	2.01	2.07	2.04	2.09	2.05	2.09	2.05	2.07			
155	2.20	2.28	2.26	2.28	2.25	2.30	2.26	2.28	2.22	2.28	2.26	2.30	2.25	2.28	2.26	2.28			
160	2.43	2.49	2.45	2.50	2.47	2.50	2.46	2.50	2.44	2.50	2.46	2.50	2.47	2.50	2.45	2.49			
165	2.60	2.66	2.62	2.68	2.63	2.67	2.63	2.68	2.61	2.68	2.63	2.67	2.63	2.68	2.62	2.66			
170	2.73	2.78	2.74	2.80	2.75	2.81	2.77	2.80	2.73	2.80	2.77	2.81	2.75	2.80	2.74	2.78			
175	2.83	2.85	2.83	2.86	2.82	2.86	2.84	2.87	2.83	2.87	2.84	2.86	2.82	2.86	2.83	2.85			
180	2.88	2.88	2.87	2.87	2.86	2.86	2.87	2.87	2.88	2.87	2.87	2.86	2.86	2.87	2.87	2.88			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9788]
 Remarks: