


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.5V I:0.1656A P:35.25W PF:0.9655 Lamp Flux:3729.22x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 105.79 lm/W			
MODEL	PL-6262-36D	Imax(cd)	1704	S/MH(C0/180)	1.26
NOMINAL POWER(W)	36	LOR(%)	100.0	S/MH(C90/270)	1.23
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	3729.2	η UP,DN(C0-180)	0.1,49.9
NOMINAL FLUX(lm)	3729.22	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.1,49.9
LAMPS INSIDE	1	η up(%)	0.2	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	220	η down(%)	99.8	CIBSE SHR MAX	1.25

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:ZYP
Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:25%
Test Distance:7.560m [K=0.9325]
Remarks:

ZONAL FLUX DIAGRAM AND LUMINANCE LIMITATION CURVES

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	$\%lum, lamp$
10	1676	1681	1685	1683	1678	1683	1685	1681	0- 10	160.8	160.8	4.31,4.31
20	1628	1650	1664	1643	1618	1643	1664	1650	10- 20	471.8	632.6	17,17
30	1478	1513	1558	1517	1467	1517	1558	1513	20- 30	732.7	1365	36.6,36.6
40	1162	1057	1059	1029	1103	1029	1059	1057	30- 40	835.8	2201	59,59
50	670.2	639.5	587.0	643.3	685.2	643.3	587.0	639.5	40- 50	629.1	2830	75.9,75.9
60	279.2	375.8	314.0	369.1	280.4	369.1	314.0	375.8	50- 60	421.7	3252	87.2,87.2
70	213.3	185.9	192.3	181.3	212.2	181.3	192.3	185.9	60- 70	252.9	3505	94,94
80	101.2	105.2	101.7	110.0	117.7	110.0	101.7	105.2	70- 80	159.2	3664	98.3,98.3
90	0.6958	0.3894	0.5035	0.3427	0.4367	0.3427	0.5035	0.3894	80- 90	58.44	3723	99.8,99.8
100	0.3290	0.3406	0.3248	0.3250	0.3250	0.3250	0.3248	0.3406	90-100	0.3447	3723	99.8,99.8
110	0.5127	0.5327	0.5089	0.5325	0.5249	0.5325	0.5089	0.5327	100-110	0.4570	3723	99.8,99.8
120	0.8341	0.8614	0.8497	0.8538	0.8575	0.8538	0.8497	0.8614	110-120	0.6847	3724	99.9,99.9
130	1.214	1.265	1.273	1.272	1.245	1.272	1.273	1.265	120-130	0.9588	3725	99.9,99.9
140	1.559	1.621	1.645	1.625	1.590	1.625	1.645	1.621	130-140	1.124	3726	99.9,99.9
150	1.919	1.985	1.989	1.978	1.951	1.978	1.989	1.985	140-150	1.132	3727	99.9,99.9
160	2.346	2.373	2.393	2.385	2.369	2.385	2.393	2.373	150-160	1.010	3728	100,100
170	2.648	2.663	2.671	2.679	2.659	2.679	2.671	2.663	160-170	0.7203	3729	100,100
180	2.793	2.781	2.773	2.785	2.793	2.785	2.773	2.781	170-180	0.2610	3729	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=0.9325]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.5V I:0.1656A P:35.25W PF:0.9655 Lamp Flux:3729.22x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0														
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
pfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Coefficients of Utilization(CU)														
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00														
1.0	1.06	1.02	.99	1.04	1.00	.97	.99	.97	.94	.96	.93	.91	.92	.90	.89	.87														
2.0	.94	.88	.83	.92	.87	.82	.89	.84	.80	.86	.82	.79	.83	.80	.77	.75														
3.0	.84	.77	.71	.83	.76	.71	.80	.74	.70	.77	.72	.68	.75	.71	.67	.65														
4.0	.76	.68	.62	.75	.67	.62	.72	.66	.61	.70	.65	.60	.68	.63	.59	.57														
5.0	.69	.61	.55	.68	.60	.54	.66	.59	.54	.64	.58	.53	.62	.57	.53	.51														
6.0	.63	.54	.49	.62	.54	.48	.60	.53	.48	.58	.52	.48	.57	.51	.47	.45														
7.0	.57	.49	.44	.57	.49	.43	.55	.48	.43	.54	.47	.43	.52	.47	.43	.41														
8.0	.53	.45	.39	.52	.44	.39	.51	.44	.39	.50	.43	.39	.48	.43	.39	.37														
9.0	.49	.41	.36	.48	.41	.36	.47	.40	.36	.46	.40	.35	.45	.39	.35	.33														
10.0	.45	.38	.33	.45	.37	.33	.44	.37	.33	.43	.37	.32	.42	.36	.32	.31														



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=0.9325]
 Remarks:

WEC AND CCEC

Test:U:220.5V I:0.1656A P:35.25W PF:0.9655 Lamp Flux:3729.22x1 lm					
NAME: Panel light			TYPE:LED		WEIGHT:
SPEC.:6262			DIM.: 620*620		SERIAL No.:1
MFR.: JT			SUR.:0.62*0.62		Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.269	.153	.048	.262	.149	.047	.249	.143	.046	.237	.136	.044	.225	.131	.042		
2.0	.254	.139	.043	.248	.136	.042	.236	.131	.041	.226	.127	.040	.216	.122	.039		
3.0	.237	.126	.038	.232	.124	.037	.222	.120	.037	.213	.116	.036	.204	.113	.035		
4.0	.221	.115	.034	.217	.113	.034	.208	.110	.033	.200	.107	.032	.192	.104	.032		
5.0	.207	.105	.031	.203	.104	.030	.195	.101	.030	.187	.099	.029	.181	.097	.029		
6.0	.194	.097	.028	.190	.096	.028	.183	.094	.027	.176	.092	.027	.170	.090	.027		
7.0	.182	.090	.025	.178	.089	.025	.172	.087	.025	.166	.085	.025	.161	.084	.025		
8.0	.171	.084	.024	.168	.083	.023	.163	.081	.023	.157	.080	.023	.152	.078	.023		
9.0	.161	.078	.022	.159	.077	.022	.154	.076	.022	.149	.075	.021	.145	.073	.021		
10.0	.153	.073	.020	.150	.073	.020	.146	.071	.020	.142	.070	.020	.137	.069	.020		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.192	.192	.192	.164	.164	.164	.112	.112	.112	.064	.064	.064	.021	.021	.021		
1.0	.179	.158	.139	.153	.135	.120	.105	.093	.083	.060	.054	.048	.019	.017	.016		
2.0	.169	.133	.104	.144	.115	.090	.099	.079	.063	.057	.046	.037	.018	.015	.012		
3.0	.160	.115	.080	.137	.100	.070	.094	.069	.049	.054	.040	.029	.017	.013	.009		
4.0	.151	.102	.064	.130	.088	.055	.089	.061	.039	.052	.036	.023	.017	.012	.008		
5.0	.144	.091	.052	.124	.079	.045	.085	.055	.032	.049	.032	.019	.016	.011	.006		
6.0	.137	.082	.043	.118	.071	.038	.081	.050	.027	.047	.029	.016	.015	.010	.005		
7.0	.130	.075	.037	.112	.065	.032	.077	.046	.023	.045	.027	.014	.015	.009	.004		
8.0	.124	.070	.032	.107	.060	.028	.074	.042	.020	.043	.025	.012	.014	.008	.004		
9.0	.119	.065	.028	.102	.056	.025	.071	.039	.017	.041	.023	.010	.013	.008	.003		
10.0	.113	.060	.025	.098	.052	.022	.068	.037	.016	.040	.022	.009	.013	.007	.003		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9325]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.5V I:0.1656A P:35.25W PF:0.9655 Lamp Flux:3729.22x1 lm										
NAME: Panel light					TYPE:LED			WEIGHT:		
SPEC.:6262					DIM.: 620*620			SERIAL No.:1		
MFR.: JT					SUR.:0.62*0.62			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	14.9	16.2	15.1	16.4	16.6	14.6	16.0	14.9	16.2	16.4
3H	15.8	17.0	16.0	17.2	17.5	15.4	16.7	15.7	16.9	17.2
4H	16.3	17.5	16.6	17.7	18.0	15.9	17.1	16.2	17.3	17.6
6H	16.7	17.8	17.0	18.1	18.3	16.3	17.4	16.6	17.7	18.0
8H	16.9	17.9	17.2	18.2	18.5	16.5	17.6	16.9	17.9	18.2
12H	17.0	18.0	17.3	18.3	18.6	16.7	17.8	17.1	18.1	18.4
4H 2H	15.2	16.4	15.5	16.6	16.9	15.0	16.2	15.3	16.4	16.7
3H	16.3	17.3	16.7	17.6	17.9	16.0	17.0	16.3	17.3	17.6
4H	17.0	17.9	17.3	18.2	18.6	16.6	17.5	17.0	17.9	18.2
6H	17.5	18.4	17.9	18.7	19.1	17.2	18.1	17.6	18.4	18.8
8H	17.8	18.6	18.2	18.9	19.3	17.5	18.3	17.9	18.7	19.1
12H	18.0	18.7	18.4	19.1	19.5	17.8	18.5	18.2	18.9	19.3
8H 4H	17.2	17.9	17.6	18.3	18.7	16.8	17.6	17.3	18.0	18.4
6H	17.9	18.5	18.3	19.0	19.4	17.7	18.3	18.1	18.7	19.1
8H	18.3	18.8	18.7	19.2	19.7	18.1	18.7	18.6	19.1	19.5
12H	18.5	19.0	19.0	19.5	19.9	18.5	19.0	19.0	19.4	19.9
12H 4H	17.2	17.9	17.6	18.3	18.7	16.9	17.6	17.3	18.0	18.4
6H	18.0	18.6	18.4	19.0	19.4	17.8	18.3	18.2	18.8	19.2
8H	18.4	18.9	18.9	19.3	19.8	18.2	18.7	18.7	19.2	19.7
Variations with the observer position at spacings:										
S = 1.0H	+ 0.3 / - 0.5					+ 0.4 / - 0.4				
1.5H	+ 0.2 / - 0.3					+ 0.3 / - 0.2				
2.0H	+ 0.7 / - 1.1					+ 0.6 / - 0.7				

CIE Pub.117 Corrected 3729 lm Total Lamp Luminous Flux.(8log(F/F0) = 4.6)

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9325]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.5V I:0.1656A P:35.25W PF:0.9655 Lamp Flux:3729.22x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	66	56	50	65	56	50	64	55	50	44
0.80	76	66	60	75	65	59	73	65	59	53
1.00	83	74	68	82	73	67	80	74	67	61
1.25	90	81	75	88	80	74	86	79	74	67
1.50	94	86	80	92	85	79	90	83	78	72
2.00	99	92	87	98	91	86	94	89	85	78
2.50	103	96	91	101	95	90	97	92	88	81
3.00	105	100	95	103	98	94	99	95	92	84
4.00	109	104	100	106	102	98	102	99	96	87
5.00	110	106	103	108	104	101	104	101	98	90
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9325]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.5V I:0.1656A P:35.25W PF:0.9655 Lamp Flux:3729.22x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:

Conical surface Flux(90deg):

2544.8 lm

%lum = 68.2%


%lamp = 68.2%

Conical surface Flux(120deg):

3252 lm

%lum = 87.2%

%lamp = 87.2%




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:ZYP
Test Date:2020-05-16

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:25%
Test Distance:7.560m [K=0.9325]
Remarks:

AAI Figure

Test:U:220.5V I:0.1656A P:35.25W PF:0.9655 Lamp Flux:3729.22x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=0.9325]
 Remarks:

ISOLUX DIAGRAM

Test:U:220.5V I:0.1656A P:35.25W PF:0.9655 Lamp Flux:3729.22x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9325]
 Remarks:

LED Avg.L Report

Test:U:220.5V I:0.1656A P:35.25W PF:0.9655 Lamp Flux:3729.22x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:6262	DIM.: 620*620	SERIAL No.:1
MFR.: JT	SUR.:0.62*0.62	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	1500
L_0~180(75)av	1653
L_0~180(85)av	1562
L_90~270(65)av	1596
L_90~270(75)av	1398
L_90~270(85)av	1843
L_45(65)av	1594
L_45(75)av	1481
L_45(85)av	1666

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9325]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: ZYP
Test Date: 2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 25%
Test Distance: 7.560m [K=0.9325]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.5V I:0.1656A P:35.25W PF:0.9655 Lamp Flux:3729.22x1 lm																		
NAME: Panel light									TYPE:LED					WEIGHT:				
SPEC.:6262									DIM.: 620*620					SERIAL No.:1				
MFR.: JT									SUR.:0.62*0.62					Shielding Angle:				

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1683	1684	1687	1683	1683	1685	1684	1684	1684	1684	1684	1685	1683	1683	1687	1684			
5	1683	1680	1676	1685	1686	1687	1686	1685	1686	1685	1686	1687	1686	1685	1676	1680			
10	1676	1673	1681	1686	1685	1686	1683	1678	1678	1678	1683	1686	1685	1686	1681	1673			
15	1662	1657	1667	1679	1678	1682	1670	1655	1658	1655	1670	1682	1678	1679	1667	1657			
20	1628	1624	1650	1658	1664	1660	1643	1623	1618	1623	1643	1660	1664	1658	1650	1624			
25	1562	1567	1591	1617	1623	1615	1591	1566	1551	1566	1591	1615	1623	1617	1591	1567			
30	1478	1484	1513	1554	1558	1550	1517	1479	1467	1479	1517	1550	1558	1554	1513	1484			
35	1374	1357	1367	1397	1392	1377	1360	1344	1349	1344	1360	1377	1392	1397	1367	1357			
40	1162	1120	1057	1053	1059	1035	1029	1082	1103	1082	1029	1035	1059	1053	1057	1120			
45	887	820	808	809	743	813	791	767	854	767	791	813	743	809	808	820			
50	670	606	639	617	587	637	643	584	685	584	643	637	587	617	639	606			
55	451	478	512	444	453	457	463	493	438	493	463	457	453	444	512	478			
60	279	378	376	325	314	343	369	327	280	327	369	343	314	325	376	378			
65	218	266	269	251	256	223	243	262	263	262	243	223	256	251	269	266			
70	213	217	186	176	192	176	181	208	212	208	181	176	192	176	186	217			
75	166	154	143	152	137	151	148	158	159	158	148	151	137	152	143	154			
80	101	102	105	109	102	111	110	93.4	118	93.4	110	111	102	109	105	102			
85	50.0	49.9	55.7	59.6	61.1	63.9	54.6	48.5	53.4	48.5	54.6	63.9	61.1	59.6	55.7	49.9			
90	0.70	0.64	0.39	0.64	0.50	0.35	0.34	0.36	0.44	0.36	0.34	0.35	0.50	0.64	0.39	0.64			
95	0.29	0.32	0.30	0.31	0.29	0.31	0.29	0.31	0.29	0.31	0.29	0.31	0.29	0.31	0.30	0.32			
100	0.33	0.38	0.34	0.36	0.32	0.36	0.32	0.37	0.33	0.37	0.32	0.36	0.32	0.36	0.34	0.38			
105	0.41	0.45	0.42	0.44	0.41	0.44	0.41	0.45	0.41	0.45	0.41	0.44	0.41	0.44	0.42	0.45			
110	0.51	0.56	0.53	0.55	0.51	0.55	0.53	0.56	0.52	0.56	0.53	0.55	0.51	0.55	0.53	0.56			
115	0.66	0.71	0.68	0.71	0.66	0.69	0.67	0.71	0.67	0.71	0.67	0.69	0.66	0.71	0.68	0.71			
120	0.83	0.89	0.86	0.89	0.85	0.87	0.85	0.89	0.86	0.89	0.85	0.87	0.85	0.89	0.86	0.89			
125	1.03	1.08	1.06	1.09	1.06	1.10	1.06	1.09	1.05	1.09	1.06	1.10	1.06	1.09	1.06	1.08			
130	1.21	1.29	1.26	1.30	1.27	1.31	1.27	1.30	1.25	1.30	1.27	1.31	1.27	1.30	1.26	1.29			
135	1.38	1.46	1.44	1.49	1.46	1.49	1.44	1.46	1.41	1.46	1.44	1.49	1.46	1.49	1.44	1.46			
140	1.56	1.64	1.62	1.66	1.64	1.67	1.63	1.64	1.59	1.64	1.63	1.67	1.64	1.66	1.62	1.64			
145	1.74	1.82	1.80	1.83	1.81	1.84	1.79	1.82	1.76	1.82	1.79	1.84	1.81	1.83	1.80	1.82			
150	1.92	2.00	1.99	2.02	1.99	2.02	1.98	2.00	1.95	2.00	1.98	2.02	1.99	2.02	1.99	2.00			
155	2.12	2.21	2.18	2.22	2.19	2.22	2.19	2.21	2.15	2.21	2.19	2.22	2.19	2.22	2.18	2.21			
160	2.35	2.41	2.37	2.42	2.39	2.42	2.39	2.41	2.37	2.41	2.39	2.42	2.39	2.42	2.37	2.41			
165	2.52	2.58	2.53	2.59	2.56	2.59	2.56	2.59	2.53	2.59	2.56	2.59	2.56	2.59	2.53	2.58			
170	2.65	2.69	2.66	2.71	2.67	2.71	2.68	2.71	2.66	2.71	2.68	2.71	2.67	2.71	2.66	2.69			
175	2.74	2.77	2.74	2.77	2.74	2.78	2.75	2.78	2.75	2.78	2.75	2.78	2.74	2.77	2.74	2.77			
180	2.79	2.79	2.78	2.79	2.77	2.78	2.78	2.78	2.79	2.78	2.78	2.78	2.77	2.79	2.78	2.79			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-16

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9325]
 Remarks: