


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.7V I:0.1648A P:35.11W PF:0.9657 Lamp Flux:3555.4lx1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 101.26 lm/W			
MODEL	PL-3012-36D	Imax(cd)	1623	S/MH(C0/180)	1.28
NOMINAL POWER(W)	36	LOR(%)	100.0	S/MH(C90/270)	1.23
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	3555.4	η UP,DN(C0-180)	0.1,50.0
NOMINAL FLUX(lm)	3555.41	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.1,49.8
LAMPS INSIDE	1	η up(%)	0.2	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	220	η down(%)	99.8	CIBSE SHR MAX	1.30

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9392]
 Remarks:

ZONAL FLUX DIAGRAM AND LUMINANCE LIMITATION CURVES

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	$\%lum, lamp$
10	1623	1616	1605	1613	1616	1613	1605	1616	0- 10	154.2	154.2	4.34,4.34
20	1604	1577	1546	1570	1595	1570	1546	1577	10- 20	452.4	606.6	17.1,17.1
30	1500	1456	1407	1449	1486	1449	1407	1456	20- 30	701.9	1309	36.8,36.8
40	1129	1048	1004	1009	1094	1009	1004	1048	30- 40	807.2	2116	59.5,59.5
50	693.2	619.0	533.3	595.4	628.9	595.4	533.3	619.0	40- 50	605.2	2721	76.5,76.5
60	278.7	362.3	284.9	329.8	254.6	329.8	284.9	362.3	50- 60	398.3	3119	87.7,87.7
70	201.4	177.2	166.6	163.1	191.5	163.1	166.6	177.2	60- 70	234.9	3354	94.3,94.3
80	110.5	100.6	90.84	90.93	86.76	90.93	90.84	100.6	70- 80	143.1	3497	98.4,98.4
90	3.421	1.923	0.3014	0.3465	0.5953	0.3465	0.3014	1.923	80- 90	51.75	3549	99.8,99.8
100	0.2540	0.2859	0.3017	0.2979	0.2780	0.2979	0.3017	0.2859	90-100	0.3440	3549	99.8,99.8
110	0.4288	0.4726	0.5003	0.5003	0.4806	0.5003	0.5003	0.4726	100-110	0.4163	3550	99.8,99.8
120	0.7344	0.7743	0.8140	0.8257	0.8099	0.8257	0.8140	0.7743	110-120	0.6394	3550	99.9,99.9
130	1.140	1.164	1.176	1.223	1.247	1.223	1.176	1.164	120-130	0.8999	3551	99.9,99.9
140	1.509	1.537	1.541	1.565	1.609	1.565	1.541	1.537	130-140	1.072	3552	99.9,99.9
150	1.839	1.930	1.915	1.903	1.950	1.903	1.915	1.930	140-150	1.094	3553	99.9,99.9
160	2.256	2.323	2.268	2.260	2.367	2.260	2.268	2.323	150-160	0.9757	3554	100,100
170	2.653	2.598	2.542	2.566	2.741	2.566	2.542	2.598	160-170	0.6977	3555	100,100
180	2.820	2.717	2.677	2.701	2.836	2.701	2.677	2.717	170-180	0.2554	3555	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=0.9392]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.7V I:0.1648A P:35.11W PF:0.9657 Lamp Flux:3555.4lx1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.06	1.02	.99	1.04	1.01	.97	.00	.97	.94	.96	.94	.91	.92	.90	.89	.87
2.0	.95	.89	.84	.93	.87	.83	.89	.85	.81	.86	.82	.79	.83	.80	.77	.75
3.0	.85	.78	.72	.83	.77	.71	.80	.75	.70	.78	.73	.69	.75	.71	.68	.66
4.0	.76	.68	.62	.75	.68	.62	.73	.66	.61	.70	.65	.60	.68	.64	.60	.58
5.0	.69	.61	.55	.68	.60	.55	.66	.59	.54	.64	.58	.54	.62	.57	.53	.51
6.0	.63	.55	.49	.62	.54	.49	.60	.53	.48	.59	.53	.48	.57	.52	.48	.46
7.0	.58	.50	.44	.57	.49	.44	.55	.48	.43	.54	.48	.43	.53	.47	.43	.41
8.0	.53	.45	.40	.52	.45	.40	.51	.44	.39	.50	.44	.39	.49	.43	.39	.37
9.0	.49	.41	.36	.48	.41	.36	.47	.40	.36	.46	.40	.36	.45	.40	.35	.34
10.0	.45	.38	.33	.45	.38	.33	.44	.37	.33	.43	.37	.33	.42	.36	.32	.31



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9392]
 Remarks:

WEC AND CCEC

Test:U:220.7V I:0.1648A P:35.11W PF:0.9657 Lamp Flux:3555.4lx1 lm					
NAME: Panel light			TYPE:LED		WEIGHT:
SPEC.:3012			DIM.: 1195*295		SERIAL No.:01
MFR.: JT			SUR.:0.295*1.195		Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.266	.151	.048	.259	.148	.047	.246	.141	.045	.234	.135	.043	.223	.129	.042	
2.0	.252	.138	.042	.246	.135	.042	.234	.130	.040	.224	.125	.039	.214	.121	.038	
3.0	.236	.125	.038	.230	.123	.037	.220	.119	.036	.211	.116	.035	.202	.112	.035	
4.0	.220	.114	.034	.215	.113	.033	.206	.110	.033	.198	.106	.032	.191	.104	.032	
5.0	.206	.105	.030	.202	.103	.030	.194	.101	.030	.186	.098	.029	.180	.096	.029	
6.0	.193	.097	.028	.189	.096	.027	.182	.093	.027	.176	.091	.027	.170	.089	.027	
7.0	.181	.090	.025	.178	.089	.025	.172	.087	.025	.166	.085	.025	.160	.083	.024	
8.0	.171	.083	.023	.168	.083	.023	.162	.081	.023	.157	.079	.023	.152	.078	.023	
9.0	.161	.078	.022	.158	.077	.022	.153	.076	.021	.149	.075	.021	.144	.073	.021	
10.0	.152	.073	.020	.150	.072	.020	.145	.071	.020	.141	.070	.020	.137	.069	.020	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.192	.192	.192	.164	.164	.164	.112	.112	.112	.064	.064	.064	.021	.021	.021	
1.0	.179	.158	.139	.153	.136	.120	.105	.093	.083	.060	.054	.048	.019	.017	.016	
2.0	.168	.133	.104	.144	.115	.090	.099	.080	.063	.057	.046	.037	.018	.015	.012	
3.0	.159	.115	.081	.137	.100	.070	.094	.069	.049	.054	.040	.029	.017	.013	.009	
4.0	.151	.102	.064	.130	.088	.056	.089	.061	.039	.052	.036	.023	.017	.012	.008	
5.0	.144	.091	.052	.123	.079	.045	.085	.055	.032	.049	.032	.019	.016	.011	.006	
6.0	.137	.082	.044	.117	.071	.038	.081	.050	.027	.047	.029	.016	.015	.010	.005	
7.0	.130	.075	.037	.112	.065	.032	.077	.046	.023	.045	.027	.014	.015	.009	.005	
8.0	.124	.070	.032	.107	.060	.028	.074	.042	.020	.043	.025	.012	.014	.008	.004	
9.0	.119	.065	.028	.102	.056	.025	.071	.039	.017	.041	.023	.010	.013	.008	.003	
10.0	.113	.060	.025	.098	.052	.022	.068	.037	.016	.040	.022	.009	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9392]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.7V I:0.1648A P:35.11W PF:0.9657 Lamp Flux:3555.4lx1 lm										
NAME: Panel light					TYPE:LED			WEIGHT:		
SPEC.:3012					DIM.: 1195*295			SERIAL No.:01		
MFR.: JT					SUR.:0.295*1.195			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	15.2	16.5	15.4	16.7	16.9	14.7	16.0	14.9	16.2	16.4
3H	16.1	17.3	16.4	17.5	17.8	15.4	16.6	15.6	16.8	17.1
4H	16.6	17.7	16.9	18.0	18.2	15.8	17.0	16.1	17.2	17.4
6H	17.0	18.1	17.3	18.3	18.6	16.2	17.3	16.5	17.5	17.8
8H	17.1	18.2	17.5	18.5	18.8	16.4	17.4	16.7	17.7	18.0
12H	17.3	18.3	17.6	18.6	18.9	16.6	17.6	16.9	17.9	18.2
4H 2H	15.5	16.6	15.8	16.9	17.1	15.0	16.2	15.3	16.5	16.7
3H	16.6	17.6	16.9	17.9	18.2	15.9	16.9	16.3	17.2	17.5
4H	17.2	18.1	17.6	18.5	18.8	16.5	17.4	16.9	17.7	18.1
6H	17.8	18.6	18.2	18.9	19.3	17.1	17.9	17.5	18.3	18.6
8H	18.0	18.8	18.4	19.1	19.5	17.4	18.1	17.8	18.5	18.9
12H	18.2	18.9	18.6	19.3	19.7	17.6	18.3	18.1	18.7	19.1
8H 4H	17.4	18.1	17.8	18.5	18.9	16.8	17.5	17.2	17.9	18.3
6H	18.1	18.7	18.5	19.1	19.6	17.5	18.2	18.0	18.6	19.0
8H	18.4	19.0	18.9	19.4	19.9	17.9	18.5	18.4	18.9	19.4
12H	18.7	19.2	19.2	19.7	20.1	18.4	18.8	18.8	19.3	19.8
12H 4H	17.4	18.1	17.8	18.5	18.9	16.8	17.5	17.2	17.9	18.3
6H	18.2	18.7	18.6	19.1	19.6	17.6	18.2	18.1	18.6	19.1
8H	18.5	19.0	19.0	19.5	19.9	18.1	18.6	18.6	19.0	19.5
Variations with the observer position at spacings:										
S = 1.0H	+ 0.3 / - 0.5					+ 0.4 / - 0.5				
1.5H	+ 0.3 / - 0.3					+ 0.3 / - 0.3				
2.0H	+ 0.7 / - 1.1					+ 0.6 / - 0.8				

CIE Pub.117 Corrected 3555 lm Total Lamp Luminous Flux.(8log(F/F0) = 4.4)

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9392]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.7V I:0.1648A P:35.11W PF:0.9657 Lamp Flux:3555.4lx1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	66	56	50	66	56	50	65	56	50	44
0.80	76	66	60	75	66	60	73	65	59	53
1.00	84	74	68	82	74	68	80	75	67	61
1.25	90	81	75	89	80	75	86	79	74	68
1.50	94	86	80	93	85	80	90	83	79	72
2.00	100	93	87	98	92	87	95	89	85	78
2.50	103	96	91	101	95	90	97	92	89	81
3.00	105	100	95	103	98	94	100	95	92	84
4.00	109	104	100	106	102	99	102	99	96	88
5.00	111	107	103	108	105	102	104	101	99	90
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9392]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.7V I:0.1648A P:35.11W PF:0.9657 Lamp Flux:3555.4lx1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:

Conical surface Flux(90deg):

2448.3 lm

%lum = 68.9%


%lamp = 68.9%

Conical surface Flux(120deg):

3119.3 lm

%lum = 87.7%

%lamp = 87.7%




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:ZYP
Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:25%
Test Distance:7.560m [K=0.9392]
Remarks:

AAI Figure

Test:U:220.7V I:0.1648A P:35.11W PF:0.9657 Lamp Flux:3555.4lx1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9392]
 Remarks:

ISOLUX DIAGRAM

Test:U:220.7V I:0.1648A P:35.11W PF:0.9657 Lamp Flux:3555.4lx1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9392]
 Remarks:

LED Avg.L Report

Test:U:220.7V I:0.1648A P:35.11W PF:0.9657 Lamp Flux:3555.4lx1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	1507
L_0~180(75)av	1617
L_0~180(85)av	1513
L_90~270(65)av	1552
L_90~270(75)av	1361
L_90~270(85)av	1733
L_45(65)av	1658
L_45(75)av	1454
L_45(85)av	1471

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9392]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: ZYP
Test Date: 2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 25%
Test Distance: 7.560m [K=0.9392]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.7V I:0.1648A P:35.11W PF:0.9657 Lamp Flux:3555.4lx1 lm																		
NAME: Panel light										TYPE:LED					WEIGHT:			
SPEC.:3012										DIM.: 1195*295					SERIAL No.:01			
MFR.: JT										SUR.:0.295*1.195					Shielding Angle:			

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1614	1614	1614	1614	1614	1614	1615	1614	1614	1614	1615	1614	1614	1614	1614	1614			
5	1617	1617	1617	1615	1615	1615	1616	1616	1616	1616	1616	1615	1615	1615	1617	1617			
10	1623	1619	1616	1609	1605	1610	1613	1615	1616	1615	1613	1610	1605	1609	1616	1619			
15	1618	1608	1603	1595	1583	1593	1599	1604	1613	1604	1599	1593	1583	1595	1603	1608			
20	1604	1592	1577	1561	1546	1558	1570	1584	1595	1584	1570	1558	1546	1561	1577	1592			
25	1564	1554	1528	1504	1488	1500	1521	1540	1550	1540	1521	1500	1488	1504	1528	1554			
30	1500	1486	1456	1424	1407	1427	1449	1472	1486	1472	1449	1427	1407	1424	1456	1486			
35	1395	1366	1313	1278	1273	1296	1319	1352	1374	1352	1319	1296	1273	1278	1313	1366			
40	1129	1113	1048	1007	1004	977	1009	1064	1094	1064	1009	977	1004	1007	1048	1113			
45	860	799	795	775	698	736	756	767	834	767	756	736	698	775	795	799			
50	693	596	619	610	533	570	595	560	629	560	595	570	533	610	619	596			
55	449	488	462	430	417	402	460	452	409	452	460	402	417	430	462	488			
60	279	354	362	312	285	290	330	341	255	341	330	290	285	312	362	354			
65	239	257	252	213	230	224	239	235	207	235	239	224	230	213	252	257			
70	201	205	177	158	167	153	163	189	192	189	163	153	167	158	177	205			
75	153	148	137	138	123	133	126	132	139	132	126	133	123	138	137	148			
80	110	89.9	101	98.9	90.8	95.2	90.9	85.6	86.8	85.6	90.9	95.2	90.8	98.9	101	89.9			
85	51.6	49.8	46.6	58.9	52.9	49.6	43.2	44.6	40.7	44.6	43.2	49.6	52.9	58.9	46.6	49.8			
90	3.42	4.44	1.92	0.73	0.30	0.24	0.35	0.48	0.60	0.48	0.35	0.24	0.30	0.73	1.92	4.44			
95	0.21	0.25	0.24	0.27	0.23	0.27	0.25	0.27	0.22	0.27	0.25	0.27	0.23	0.27	0.24	0.25			
100	0.25	0.31	0.29	0.33	0.30	0.33	0.30	0.33	0.28	0.33	0.30	0.33	0.30	0.33	0.29	0.31			
105	0.33	0.38	0.36	0.41	0.39	0.43	0.39	0.41	0.37	0.41	0.39	0.43	0.39	0.41	0.36	0.38			
110	0.43	0.49	0.47	0.52	0.50	0.54	0.50	0.52	0.48	0.52	0.50	0.54	0.50	0.52	0.47	0.49			
115	0.56	0.62	0.61	0.66	0.64	0.69	0.64	0.66	0.63	0.66	0.64	0.69	0.64	0.66	0.61	0.62			
120	0.73	0.79	0.77	0.84	0.81	0.85	0.83	0.85	0.81	0.85	0.83	0.85	0.81	0.84	0.77	0.79			
125	0.93	0.98	0.97	1.01	0.99	1.03	1.03	1.06	1.02	1.06	1.03	1.03	0.99	1.01	0.97	0.98			
130	1.14	1.18	1.16	1.20	1.18	1.22	1.22	1.28	1.25	1.28	1.22	1.22	1.18	1.20	1.16	1.18			
135	1.34	1.39	1.34	1.39	1.35	1.39	1.39	1.47	1.44	1.47	1.39	1.39	1.35	1.39	1.34	1.39			
140	1.51	1.56	1.54	1.57	1.54	1.57	1.56	1.64	1.61	1.64	1.56	1.57	1.54	1.57	1.54	1.56			
145	1.67	1.74	1.73	1.77	1.73	1.75	1.74	1.80	1.77	1.80	1.74	1.75	1.73	1.77	1.73	1.74			
150	1.84	1.95	1.93	1.97	1.91	1.95	1.90	1.95	1.95	1.95	1.90	1.95	1.91	1.97	1.93	1.95			
155	2.03	2.16	2.13	2.15	2.10	2.13	2.07	2.12	2.15	2.12	2.07	2.13	2.10	2.15	2.13	2.16			
160	2.26	2.39	2.32	2.32	2.27	2.30	2.26	2.31	2.37	2.31	2.26	2.30	2.27	2.32	2.32	2.39			
165	2.47	2.59	2.48	2.47	2.42	2.47	2.43	2.50	2.57	2.50	2.43	2.47	2.42	2.47	2.48	2.59			
170	2.65	2.73	2.60	2.58	2.54	2.58	2.57	2.65	2.74	2.65	2.57	2.58	2.54	2.58	2.60	2.73			
175	2.78	2.80	2.68	2.66	2.62	2.66	2.65	2.76	2.82	2.76	2.65	2.66	2.62	2.66	2.68	2.80			
180	2.82	2.81	2.72	2.70	2.68	2.68	2.70	2.78	2.84	2.78	2.70	2.68	2.68	2.70	2.72	2.81			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=0.9392]
 Remarks: