


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.6V I:0.1729A P:36.94W PF:0.9683 Lamp Flux:3767.2x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 101.98 lm/W			
MODEL	PL-3012-36D	Imax(cd)	1723	S/MH(C0/180)	1.28
NOMINAL POWER(W)	36	LOR(%)	100.0	S/MH(C90/270)	1.23
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	3767.2	η UP,DN(C0-180)	0.1,50.0
NOMINAL FLUX(lm)	3767.2	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.1,49.8
LAMPS INSIDE	1	η up(%)	0.2	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	220	η down(%)	99.8	CIBSE SHR MAX	1.30

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM AND LUMINANCE LIMITATION CURVES

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	$\%lum, lamp$
10	1723	1713	1701	1707	1709	1707	1701	1713	0- 10	163.4	163.4	4.34,4.34
20	1704	1673	1639	1663	1688	1663	1639	1673	10- 20	479.3	642.7	17.1,17.1
30	1593	1543	1490	1533	1573	1533	1490	1543	20- 30	743.7	1386	36.8,36.8
40	1198	1112	1065	1070	1158	1070	1065	1112	30- 40	855.7	2242	59.5,59.5
50	735.6	656.4	564.9	630.5	666.5	630.5	564.9	656.4	40- 50	641.5	2884	76.5,76.5
60	295.6	383.8	301.8	348.7	269.5	348.7	301.8	383.8	50- 60	421.9	3306	87.7,87.7
70	213.7	187.8	176.5	172.6	202.3	172.6	176.5	187.8	60- 70	248.7	3554	94.3,94.3
80	117.0	106.6	96.20	96.20	91.67	96.20	96.20	106.6	70- 80	151.4	3706	98.4,98.4
90	3.439	1.953	0.2812	0.3728	0.6136	0.3728	0.2812	1.953	80- 90	54.77	3760	99.8,99.8
100	0.2655	0.2971	0.3153	0.3150	0.2927	0.3150	0.3153	0.2971	90-100	0.3611	3761	99.8,99.8
110	0.4591	0.4905	0.5312	0.5267	0.5087	0.5267	0.5312	0.4905	100-110	0.4396	3761	99.8,99.8
120	0.7789	0.8150	0.8557	0.8687	0.8552	0.8687	0.8557	0.8150	110-120	0.6753	3762	99.9,99.9
130	1.207	1.229	1.242	1.297	1.310	1.297	1.242	1.229	120-130	0.9516	3763	99.9,99.9
140	1.608	1.630	1.630	1.644	1.698	1.644	1.630	1.630	130-140	1.137	3764	99.9,99.9
150	1.950	2.045	2.026	2.004	2.053	2.004	2.026	2.045	140-150	1.157	3765	99.9,99.9
160	2.387	2.459	2.400	2.382	2.490	2.382	2.400	2.459	150-160	1.031	3766	100,100
170	2.810	2.747	2.675	2.698	2.896	2.698	2.675	2.747	160-170	0.7372	3767	100,100
180	2.991	2.869	2.819	2.851	2.991	2.851	2.819	2.869	170-180	0.2698	3767	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.6V I:0.1729A P:36.94W PF:0.9683 Lamp Flux:3767.2x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.06	1.02	.99	1.04	1.01	.97	.00	.97	.94	.96	.94	.91	.92	.90	.89	.87
2.0	.95	.89	.84	.93	.87	.83	.89	.85	.81	.86	.82	.79	.83	.80	.77	.75
3.0	.85	.78	.72	.83	.77	.71	.80	.75	.70	.78	.73	.69	.75	.71	.68	.66
4.0	.76	.68	.62	.75	.68	.62	.73	.66	.61	.70	.65	.60	.68	.64	.60	.58
5.0	.69	.61	.55	.68	.60	.55	.66	.59	.54	.64	.58	.54	.62	.57	.53	.51
6.0	.63	.55	.49	.62	.54	.49	.60	.53	.48	.59	.53	.48	.57	.52	.48	.46
7.0	.58	.50	.44	.57	.49	.44	.55	.48	.43	.54	.48	.43	.53	.47	.43	.41
8.0	.53	.45	.40	.52	.45	.40	.51	.44	.39	.50	.44	.39	.49	.43	.39	.37
9.0	.49	.41	.36	.48	.41	.36	.47	.40	.36	.46	.40	.36	.45	.40	.35	.34
10.0	.45	.38	.33	.45	.38	.33	.44	.37	.33	.43	.37	.33	.42	.36	.32	.31



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: ZYP
Test Date: 2020-05-25

```

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:25%
Test Distance:7.560m [K=1.0000]
Remarks:

```

WEC AND CCEC

Test:U:220.6V I:0.1729A P:36.94W PF:0.9683 Lamp Flux:3767.2x1 lm								
NAME: Panel light			TYPE:LED			WEIGHT:		
SPEC.:3012			DIM.: 1195*295			SERIAL No.:01		
MFR.: JT			SUR.:0.295*1.195			Shielding Angle:		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.266	.151	.048	.259	.148	.047	.246	.141	.045	.234	.135	.043	.223	.129	.042	
2.0	.252	.138	.042	.246	.135	.042	.234	.130	.040	.224	.125	.039	.214	.121	.038	
3.0	.236	.125	.038	.230	.123	.037	.220	.119	.036	.211	.116	.035	.202	.112	.035	
4.0	.220	.114	.034	.215	.113	.033	.206	.109	.033	.198	.106	.032	.191	.104	.032	
5.0	.206	.105	.030	.202	.103	.030	.194	.101	.030	.186	.098	.029	.180	.096	.029	
6.0	.193	.097	.028	.189	.096	.027	.182	.093	.027	.176	.091	.027	.170	.089	.027	
7.0	.181	.090	.025	.178	.089	.025	.172	.087	.025	.166	.085	.025	.160	.083	.024	
8.0	.171	.083	.023	.168	.083	.023	.162	.081	.023	.157	.079	.023	.152	.078	.023	
9.0	.161	.078	.022	.158	.077	.022	.153	.076	.021	.149	.075	.021	.144	.073	.021	
10.0	.152	.073	.020	.150	.072	.020	.145	.071	.020	.141	.070	.020	.137	.069	.020	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.192	.192	.192	.164	.164	.164	.112	.112	.112	.064	.064	.064	.021	.021	.021	
1.0	.179	.158	.139	.153	.136	.120	.105	.093	.083	.060	.054	.048	.019	.017	.016	
2.0	.168	.133	.104	.144	.115	.090	.099	.080	.063	.057	.046	.037	.018	.015	.012	
3.0	.159	.115	.081	.137	.100	.070	.094	.069	.049	.054	.040	.029	.017	.013	.009	
4.0	.151	.102	.064	.130	.088	.056	.089	.061	.039	.052	.036	.023	.017	.012	.008	
5.0	.144	.091	.052	.123	.079	.045	.085	.055	.032	.049	.032	.019	.016	.011	.006	
6.0	.137	.082	.044	.117	.071	.038	.081	.050	.027	.047	.029	.016	.015	.010	.005	
7.0	.130	.075	.037	.112	.065	.032	.077	.046	.023	.045	.027	.014	.015	.009	.005	
8.0	.124	.070	.032	.107	.060	.028	.074	.042	.020	.043	.025	.012	.014	.008	.004	
9.0	.119	.065	.028	.102	.056	.025	.071	.039	.017	.041	.023	.010	.013	.008	.003	
10.0	.113	.060	.025	.098	.052	.022	.068	.037	.016	.040	.022	.009	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.6V I:0.1729A P:36.94W PF:0.9683 Lamp Flux:3767.2x1 lm												
NAME: Panel light					TYPE:LED			WEIGHT:				
SPEC.:3012					DIM.: 1195*295			SERIAL No.:01				
MFR.: JT					SUR.:0.295*1.195			Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3		
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3		
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2		
Room dimensions		Viewed crosswise					Viewed endwise					
x = 2H y = 2H	2H	15.4	16.8	15.7	16.9	17.1	14.9	16.2	15.1	16.4	16.6	
	3H	16.3	17.5	16.6	17.7	18.0	15.6	16.8	15.8	17.0	17.3	
	4H	16.8	17.9	17.1	18.2	18.4	16.0	17.1	16.3	17.4	17.6	
	6H	17.2	18.3	17.5	18.5	18.8	16.4	17.5	16.7	17.7	18.0	
	8H	17.4	18.4	17.7	18.7	19.0	16.6	17.6	16.9	17.9	18.2	
	12H	17.5	18.5	17.8	18.8	19.1	16.8	17.8	17.1	18.1	18.4	
	4H	2H	15.7	16.8	16.0	17.1	17.3	15.2	16.4	15.5	16.7	16.9
		3H	16.8	17.8	17.1	18.1	18.4	16.1	17.1	16.5	17.4	17.7
		4H	17.4	18.3	17.8	18.7	19.0	16.7	17.6	17.1	17.9	18.3
		6H	18.0	18.8	18.4	19.1	19.5	17.3	18.1	17.7	18.4	18.8
		8H	18.2	19.0	18.6	19.4	19.7	17.6	18.3	18.0	18.7	19.1
		12H	18.4	19.1	18.8	19.5	19.9	17.8	18.5	18.3	18.9	19.3
8H	4H	17.6	18.4	18.0	18.7	19.1	17.0	17.7	17.4	18.1	18.5	
	6H	18.3	18.9	18.7	19.3	19.8	17.7	18.4	18.2	18.8	19.2	
	8H	18.6	19.2	19.1	19.6	20.1	18.1	18.7	18.6	19.1	19.6	
	12H	18.9	19.4	19.4	19.9	20.3	18.6	19.0	19.0	19.5	20.0	
12H	4H	17.6	18.3	18.0	18.7	19.1	17.0	17.7	17.4	18.1	18.5	
	6H	18.4	18.9	18.8	19.4	19.8	17.8	18.4	18.3	18.8	19.3	
	8H	18.7	19.2	19.2	19.7	20.2	18.3	18.8	18.8	19.2	19.7	
Variations with the observer position at spacings:												
S = 1.0H		+ 0.3 / - 0.5					+ 0.4 / - 0.5					
1.5H		+ 0.3 / - 0.3					+ 0.3 / - 0.3					
2.0H		+ 0.7 / - 1.1					+ 0.6 / - 0.8					

CIE Pub.117 Corrected 3767 lm Total Lamp Luminous Flux.(8log(F/F0) = 4.6)

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.6V I:0.1729A P:36.94W PF:0.9683 Lamp Flux:3767.2x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	66	56	50	66	56	50	65	56	50	44
0.80	76	66	60	75	66	60	73	65	59	53
1.00	84	74	68	82	74	68	80	75	67	61
1.25	90	81	75	89	80	75	86	79	74	68
1.50	94	86	80	93	85	80	90	83	79	72
2.00	100	93	87	98	92	87	95	89	85	78
2.50	103	96	91	101	95	90	97	92	89	81
3.00	105	100	95	103	98	94	100	95	92	84
4.00	109	104	100	106	102	99	102	99	96	88
5.00	111	107	103	108	105	102	104	101	99	90
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.6V I:0.1729A P:36.94W PF:0.9683 Lamp Flux:3767.2x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:

Conical surface Flux(90deg):

2594.7 lm

%lum = 68.9%


%lamp = 68.9%

Conical surface Flux(120deg):

3305.5 lm

%lum = 87.7%

%lamp = 87.7%




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:ZYP
Test Date:2020-05-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:25%
Test Distance:7.560m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.6V I:0.1729A P:36.94W PF:0.9683 Lamp Flux:3767.2x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25DEG
 Operators: ZYP
 Test Date: 2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity: 25%
 Test Distance: 7.560m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:220.6V I:0.1729A P:36.94W PF:0.9683 Lamp Flux:3767.2x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:220.6V I:0.1729A P:36.94W PF:0.9683 Lamp Flux:3767.2x1 lm		
NAME: Panel light	TYPE:LED	WEIGHT:
SPEC.:3012	DIM.: 1195*295	SERIAL No.:01
MFR.: JT	SUR.:0.295*1.195	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	1598
L_0~180(75)av	1710
L_0~180(85)av	1601
L_90~270(65)av	1644
L_90~270(75)av	1422
L_90~270(85)av	1834
L_45(65)av	1754
L_45(75)av	1539
L_45(85)av	1558

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25DEG
 Operators:ZYP
 Test Date:2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
 Humidity:25%
 Test Distance:7.560m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25DEG
Operators: ZYP
Test Date: 2020-05-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity: 25%
Test Distance: 7.560m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.6V I:0.1729A P:36.94W PF:0.9683 Lamp Flux:3767.2x1 lm																		
NAME: Panel light									TYPE:LED					WEIGHT:				
SPEC.:3012									DIM.: 1195*295					SERIAL No.:01				
MFR.: JT									SUR.:0.295*1.195					Shielding Angle:				

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1714	1712	1712	1710	1710	1709	1708	1708	1707	1708	1708	1709	1710	1710	1712	1712			
5	1720	1717	1715	1711	1711	1710	1710	1710	1709	1710	1710	1710	1711	1711	1715	1717			
10	1723	1718	1713	1706	1701	1704	1707	1710	1709	1710	1707	1704	1701	1706	1713	1718			
15	1719	1707	1701	1691	1676	1685	1693	1697	1706	1697	1693	1685	1676	1691	1701	1707			
20	1704	1690	1673	1654	1639	1648	1663	1676	1688	1676	1663	1648	1639	1654	1673	1690			
25	1660	1648	1621	1593	1576	1589	1610	1630	1639	1630	1610	1589	1576	1593	1621	1648			
30	1593	1577	1543	1509	1490	1510	1533	1558	1573	1558	1533	1510	1490	1509	1543	1577			
35	1482	1449	1393	1355	1349	1372	1397	1432	1455	1432	1397	1372	1349	1355	1393	1449			
40	1198	1181	1112	1068	1065	1036	1070	1127	1158	1127	1070	1036	1065	1068	1112	1181			
45	913	848	842	822	740	779	801	812	884	812	801	779	740	822	842	848			
50	736	633	656	647	565	603	631	593	666	593	631	603	565	647	656	633			
55	476	518	489	455	442	426	486	478	433	478	486	426	442	455	489	518			
60	296	375	384	330	302	307	349	361	270	361	349	307	302	330	384	375			
65	254	274	266	225	243	237	252	246	219	246	252	237	243	225	266	274			
70	214	217	188	167	176	161	173	200	202	200	173	161	176	167	188	217			
75	162	157	145	146	129	141	134	140	147	140	134	141	129	146	145	157			
80	117	95.3	107	105	96.2	101	96.2	90.5	91.7	90.5	96.2	101	96.2	105	107	95.3			
85	54.5	52.9	49.3	62.4	55.9	52.6	45.8	47.2	43.1	47.2	45.8	52.6	55.9	62.4	49.3	52.9			
90	3.44	4.57	1.95	0.74	0.28	0.26	0.37	0.50	0.61	0.50	0.37	0.26	0.28	0.74	1.95	4.57			
95	0.23	0.26	0.26	0.29	0.24	0.29	0.27	0.27	0.23	0.27	0.27	0.29	0.24	0.29	0.26	0.26			
100	0.27	0.32	0.30	0.35	0.32	0.36	0.32	0.34	0.29	0.34	0.32	0.36	0.32	0.35	0.30	0.32			
105	0.35	0.41	0.38	0.44	0.41	0.45	0.41	0.44	0.38	0.44	0.41	0.45	0.41	0.44	0.38	0.41			
110	0.46	0.51	0.49	0.56	0.53	0.57	0.53	0.55	0.51	0.55	0.53	0.57	0.53	0.56	0.49	0.51			
115	0.60	0.66	0.64	0.71	0.68	0.73	0.68	0.70	0.66	0.70	0.68	0.73	0.68	0.71	0.64	0.66			
120	0.78	0.84	0.81	0.89	0.86	0.91	0.87	0.90	0.86	0.90	0.87	0.91	0.86	0.89	0.81	0.84			
125	0.99	1.03	1.02	1.08	1.04	1.09	1.08	1.12	1.08	1.12	1.08	1.09	1.04	1.08	1.02	1.03			
130	1.21	1.26	1.23	1.28	1.24	1.29	1.30	1.35	1.31	1.35	1.30	1.29	1.24	1.28	1.23	1.26			
135	1.42	1.47	1.43	1.48	1.45	1.48	1.49	1.57	1.53	1.57	1.49	1.48	1.45	1.48	1.43	1.47			
140	1.61	1.66	1.63	1.67	1.63	1.66	1.64	1.73	1.70	1.73	1.64	1.66	1.63	1.67	1.63	1.66			
145	1.77	1.86	1.83	1.88	1.82	1.86	1.83	1.90	1.87	1.90	1.83	1.86	1.82	1.88	1.83	1.86			
150	1.95	2.06	2.04	2.09	2.03	2.05	2.00	2.06	2.05	2.06	2.00	2.05	2.03	2.09	2.04	2.06			
155	2.16	2.29	2.26	2.27	2.22	2.25	2.19	2.23	2.26	2.23	2.19	2.25	2.22	2.27	2.26	2.29			
160	2.39	2.53	2.46	2.46	2.40	2.43	2.38	2.44	2.49	2.44	2.38	2.43	2.40	2.46	2.46	2.53			
165	2.62	2.74	2.63	2.61	2.55	2.59	2.57	2.64	2.71	2.64	2.57	2.59	2.55	2.61	2.63	2.74			
170	2.81	2.89	2.75	2.73	2.68	2.73	2.70	2.80	2.90	2.80	2.70	2.73	2.68	2.73	2.75	2.89			
175	2.95	2.97	2.83	2.81	2.77	2.81	2.79	2.91	2.97	2.91	2.79	2.81	2.77	2.81	2.83	2.97			
180	2.99	2.98	2.87	2.85	2.82	2.82	2.85	2.93	2.99	2.93	2.85	2.82	2.82	2.85	2.87	2.98			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25DEG
Operators:ZYP
Test Date:2020-05-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.295
Humidity:25%
Test Distance:7.560m [K=1.0000]
Remarks: