


Light Source Test Report

**CIE Color Parameters:**Chromaticity Coordinate: $x=0.3750$ $y=0.3691$ $u'=0.2246$ $v'=0.4973$ ($duv=-2.01e-003$)CCT: $T_c=4098K$ Prcp WaveL: $\lambda_c=580.0nm$ Purity=23.3%Peak WaveL: $\lambda_p=450nm$ Half Width: $\Delta\lambda=22.3nm$ Ratio: $R=18.2\%$ $G=78.1\%$ $B=3.7\%$

Average Wave: 568nm PB=3.8044 PG=3.6686 PFCLASS: ANSI_4000K 14

Rendering Index: $R_a=83.4$

R1 =82	R2 =90	R3 =94	R4 =82	R5 =82	R6 =85	R7 =86	R8 =66
--------	--------	--------	--------	--------	--------	--------	--------

R9 =12	R10=75	R11=81	R12=61	R13=84	R14=97	R15=77
--------	--------	--------	--------	--------	--------	--------

Photo Parameters:Flux: $\Phi=3725.7(lm)$ Luminous Efficacy: 103.71(lm/W) Luminous Power: $P=11.44(W)$ **Electrical Parameters:** $U=221.4V$ $I=0.1682A$ $P=35.92W$ $PF=0.965$ **Instrument Status:**

Scan Range: 380.0nm-800.0nm

Interval: 5.0nm

 $I_p = 20015(G=3,D=48)$

REF = 23652

TMP(PMT) = 28.1degrees centigrad/Test Mode: Fast Test

Product Type: PL-6262-36D
Instrument: PMS-80 System
Temperature: 25.0deg
Test Operator: ZYP

Manufacturer: JT
Test Department: JT
Humidity: 35.0%
Test Date: 2019-09-24 12:13